

MODEL	EA605	EA610	EA615	EA620	EA630
Capacity	500 VA / 300 W	1000 VA / 800 W	1500 VA / 1200 W	2000 VA / 1600 W	3000 VA / 2400 W
DC INPUT					
Rated voltage	12 V	24 V		36 V (S) 48 V (H)	48 V
DC input range (default)	10 ~ 15 V	20 ~ 30 V		30 ~ 45 V (S) 40 ~ 60 V (H)	40 ~ 60 V
AC INPUT					
AC input range (bypass mode)	0 ~ 121 / 132 / 138 / 144 Vac for 100 / 110 / 115 / 120 Vac ± 10 Vac 0 ~ 242 / 264 / 276 / 288 Vac for 200 / 220 / 230 / 240 Vac ± 10 Vac				
AC input range (mains mode)	100 V: 70 ~ 130 Vac 110 V: 80 ~ 140 Vac 115 V: 85 ~ 145 Vac 120 V: 90 ~ 150 Vac 200 V: 145 ~ 260 Vac 220 V: 165 ~ 280 Vac 230 V: 175 ~ 290 Vac 240 V: 185 ~ 300 Vac				
Frequency input range	50 Hz / 60 Hz (auto-sense), 50 Hz / 60 Hz ± 5% ~ 15%				
Generator connection	Available (generator input power is settable)				
OUTPUT					
Inverter output range	100 / 110 / 115 / 120 / 200 / 220 / 230 / 240 Vac ± 5% (settable)				
AC output range (bypass mode)	0 ~ 121 / 132 / 138 / 144 Vac for 100 / 110 / 115 / 120 Vac ± 10 Vac 0 ~ 242 / 264 / 276 / 288 Vac for 200 / 220 / 230 V / 240 Vac ± 10 Vac				
AC output range (mains mode)	100 V: 90 ~ 110 Vac 110 V: 99 ~ 121 Vac 115 V: 103 ~ 126 Vac 120 V: 108 ~ 132 Vac 200 V: 166 ~ 226 Vac 220 V: 188 ~ 245 Vac, 230 V: 199 ~ 254 Vac 240 V: 210 ~ 264 Vac				
Output frequency	50 / 60 Hz ± 0.3 Hz (settable)				
Waveform	Pure sine wave				
Inverter efficiency	Max. 75%	Max. 80%		Max. 85%	
Energy saving mode	Settable (< 3% load), enter in 80 s				
No-load shutdown	Settable (< 3% load), shut down in 80 s				
Transfer time	≤ 10 ms				
THDV (resistive load)	≤ 5%				
Protections	Overload, short circuit (inverter), battery low voltage, battery overcharge, overtemperature				
Overload (mains mode)	110% for 120 s, 125% for 60 s, 150% for 10 s (transfer to bypass mode)				
Overload (inverter mode)	110% for 60 s, 125% for 10 s, 150% for 5 s (shut down directly)				
Mute	Automatic mute in 60 s or by manual				
BATTERIES					
Inbuilt battery (standard model)	/	12 V / 7 Ah x 2	12 V / 9 Ah x 2	12 V / 9 Ah x 3	12 V / 9 Ah x 4

Charging current		Standard model (S): 1 A (default)				
		Long time model (H): 10 A (default); < 10 A, set step 1 A; ≥ 10 A, set step 5 A				
		Max. 10 A (H)	Max. 15 A (H)	/	Max. 20 A (H)	Max. 25 A (H)
Equalizing charge voltage		Single battery 14.1 Vdc (default), 13.6 ~ 15 Vdc adjustable				
Floating charge voltage		Single battery 13.5 Vdc (default), 13.2 ~ 14.6 Vdc adjustable				
Low voltage alarm point		Single battery 10.8 Vdc (default), 9.6 ~ 13 Vdc adjustable				
Low voltage shutdown point		Single battery 10.2 Vdc (default), 9.6 ~ 11.5 Vdc adjustable				
OTHERS						
Communications		USB & RJ45 (standard), dry contacts / SNMP (optional)				
Operating temperature		5°C ~ 40°C				
Operating humidity		Relative humidity ≤ 93%				
Noise level		≤ 50 dB (1 m)				
Tower	Dimensions (W × D × H) (mm)	144 x 345 x 215 (S / H)			144 x 410 x 215 (S) 144 x 345 x 215 (H)	157.5 x 460x 221.5(S) 190 x 467 x 335.5 (H)
	Packaged dimensions (W × D × H) (mm)	236 x 427 x 316 (S / H)			236 x 492 x 316 (S) 236 x 427 x 316 (H)	238 x 550 x 305 (S) 320 x 592 x 462 (H)
	Net weight (kg)	7.0 (H)	12.2 (S) 11.6 (H)	14.2 (S)	18.5 (S) 17.8 (H)	23.6(S) 28.0 (H)
	Gross weight (kg)	8.0 (H)	13.2 (S) 12.6 (H)	15.2 (S)	19.8 (S) 18.8 (H)	25 (S) 30.0 (H)
Rack mount	Dimensions (W × D × H) (mm)	--	440 × 338 × 88 (S)	440 × 410 × 132 (S)		
	Packaged dimensions (W × D × H) (mm)	--	611 × 448 × 208 (S)	611 × 505 × 235 (S)		
	Net weight (kg)	--	14.6 (S)	17.2 (S)	21.3 (S)	26.7 (S)
	Gross weight (kg)	--	16.8 (S)	20.4 (S)	24.5 (S)	30.5 (S)