

Specifications

MODEL	EA806 (1:1)	EA810 (1:1)	EA810 (3:1)	EA815 (3:1)	EA820 (3:1)	EA830 (3:1)
Capacity	6 kVA / 4800 W	10 kVA / 8 kW	10 kVA / 8 kW	15 kVA / 12 kW	20 kVA / 16 kW	30 kVA / 24 kW
INPUT						
Input wiring	Single-phase three-wire (1Φ + N + PE)		Three-phase five-wire (3Φ + N + PE)			
Rated voltage	220 / 230 / 240 Vac		380 / 400 / 415 Vac			
Voltage range	165 ~ 275 Vac		285 ~ 475 Vac			
Rated frequency	50 / 60 Hz					
Frequency range	40 ~ 70 Hz					
Bypass voltage range	± 25% (settable)					
OUTPUT						
Output wiring	Single-phase three-wire (1Φ + N + PE)					
Rated voltage	220 / 230 / 240 Vac					
Output voltage regulation	± 1%					
Rated frequency	50 / 60 Hz (settable)					
Output frequency regulation	50 / 60 Hz ± 0.1 Hz in battery mode					
Waveform	Sinusoidal					
Power factor	0.8					
Voltage distortion (THDv)	≤ 2% (linear load); ≤ 5% (non-linear load)					
Crest factor	3:1					
Overload	105% ~ 125% for 10 min, 125% ~ 150% for 1 min, 150% ~ 200% for 200 ms, > 200% for 100 ms					
BATTERIES						
DC voltage	192 Vdc					
Number of batteries	12 V × 16 pcs					
Charging voltage	216 Vdc					
EOD	168 Vdc					
Charging current	Default 8 A (2 A / 4 A / 6 A / 8 A / 10 A / 12 A selectable)					
SYSTEM						
Max. number of parallel connections	/	2				
Protections	Short-circuit, overload, overvoltage, undervoltage, low battery, overtemperature					
Communications	RS232 / USB (standard); RS485 / SNMP / dry contacts (optional)					
OTHERS						
Operating temperature	0 ~ 40°C					
Storage temperature	- 25°C ~ 55°C (without batteries)					
Relative humidity	0 ~ 95% (non-condensing)					
Altitude	≤ 1000 m (derating 1% for each additional 100 m)					
IP rating	IP 20					
Noise level at 1 m	< 60 dB					
Dimensions (W × D × H) (mm)	210 × 585 × 590	310 × 600 × 880		400 × 815 × 1100		
Packaged dimensions (W × D × H) (mm)	328 × 716 × 805	430 × 710 × 1080		525 × 925 × 1305		
Net weight (kg)	54	104	140	210	240	280
Gross weight (kg)	64	113	153	225	255	295

- All specifications subject to change without notice.
- Custom-made specifications are acceptable.
- This product is applicable to industrial, commercial, financial, rail transit and other industries applications, but not available for life support systems.
- For critical systems related to public safety or significant economic benefits, dual power system is required to power the load.