

Specifications

MODEL	EA9940	EA9960	EA9980	EA99100	EA99120	EA99160	EA99200
Capacity	40 kVA/40 kW	60 kVA/60 kW	80 kVA/80 kW	100 kVA/100 kW	120 kVA/120 kW	160 kVA/160 kW	200 kVA/200 kW
INPUT							
Input wiring	Three-phase five-wire (3Φ + N + PE)						
Rated voltage	380 / 400 / 415 Vac						
Voltage range	304 ~ 485 Vac (no downgrading), 138 ~ 304 Vac (linear downgrading between 40% ~ 100% load)						
Rated frequency	50 / 60 Hz (auto-sensing)						
Frequency range	40 ~ 70 Hz						
Power factor	≥ 0.99						
Bypass voltage range	-60% ~ +20% (settable)						
Total harmonic distortion (THDi)	≤ 3%						
OUTPUT							
Output wiring	Three-phase five-wire (3Φ + N + PE)						
Rated voltage	380 / 400 / 415 Vac						
Voltage regulation	± 1%						
Frequency	Synchronized with utility in mains mode, 50 / 60 Hz ± 0.1% in battery mode						
Waveform	Sinusoidal						
Power factor	1						
Total harmonic distortion (THDv)	≤ 1% (linear load); ≤ 4% (non-linear load)						
Crest factor	3:1						
Overload	105% ~ 110% for 60 min, 110% ~ 125% for 10 min, 125% ~ 150% for 1 min, > 150% for 0.2 s						
BATTERIES							
DC voltage	± 192 Vdc (± 180 ~ ± 264 Vdc settable) 40 kVA built-in battery: ± 240 Vdc (80 pcs 9 Ah/12 V)						
Number of battery	32 pcs (30 ~ 44 pcs settable)						
Charging current (max.)	12 A	24 A	36 A	48 A			
Recharge time	Depend on the capacity of battery						
SYSTEM							
Efficiency	Max. 96% in online mode, 99% in ECO mode						
Transfer time	0 ms						
Protections	Short-circuit, overload, overtemperature, excessive low battery, overvoltage, undervoltage, fans failure						
Max. number of parallel connections	4						
Communications	Standard configuration: RS232, USB, RS485, RJ45, dry contacts; Optional configuration: SNMP card, Wi-Fi card, GPRS card						
Display	5 inches colorful LCD touch screen						
OTHERS							
Operating temperature	0°C~40°C						
Storage temperature	-25°C~55°C (without battery)						
Relative humidity	0% ~ 95% (non-condensing)						
Altitude	≤ 1000 m; above 1000 m, downgrading 1% for each additional 100 m						
IP rating	IP 20						
Noise level at 1 m	≤ 65 dB						
Dimensions (W × D × H) (mm)	360 × 850 × 885	360 × 850 × 950	360 × 850 × 1200	440 × 850 × 1200		600 × 850 × 1200	
Packaged dimensions (W × D × H) (mm)	450 × 940 × 1055	450 × 940 × 1120	450 × 940 × 1370	530 × 940 × 1370		700 × 950 × 1370	
Net weight (kg)	95, 295 (built-in BAT)	130	156	158	198	250	300
Gross weight (kg)	110, 310 (built-in BAT)	145	172	180	220	275	325

- All specifications are subject to change without notice.
- Custom-made specifications are acceptable.
- Derate capacity to 90% when the number of batteries is set to 30 pcs.